

MONZONE®

Monzone Air-Conditioning Pte Ltd
Monzone Gul Lane
6 Gul Lane, Singapore 629405
(65) 6365 1315

Monzone Woodlands
101 Woodlands Avenue 12,
#01-12 Polaris @ Woodlands
Singapore 737719
(65) 8500 1315 (65) 6365 1315

Monzone Group
Johor (HQ)
Lot 7015, Jalan Lagenda 1, 81000,
Kulai, Johor, Malaysia
(607) 663 1315
Hotline: +6016 262 1315

Shah Alam
No. 4, Jalan Sg Pelubung 32/149,
Seksyen 32, 40460 Shah Alam,
Selangor, Malaysia
(603) 5525 1153
Hotline: +6016 262 1315

Kedah
No. 16 Taman Jitra Jaya, 06000
Jitra, Kedah, Malaysia
(604) 917 2261
Hotline: +6016 262 1315

Penang
No. 12 Lorong Iks Bukit Tengah,
Taman Iks Bukit Tengah, 14000
Bukit Mertajam Pulau Pinang,
Malaysia
(604) 507 2315
Hotline: +6016 262 1315

Sarawak
Lot 1993, Section 66, Kuching Town,
Land District, Jalan Semangat,
Pending Industrial Estate,
93450 Kuching, Sarawak, Malaysia
(608) 233 5113
Hotline: +6016 262 1315

Sabah
Lot 27, Jalan Papar Lama, Lok Kawi
Industrial Estate, Phase 2B, 89600
Kota Kinabalu, Sabah, Malaysia
(607) 663 1315
Hotline: +6016 262 1315

Monzone Air-Conditioning Inc
Philippines
7th Floor, Unit B, 8 Rockwell,
Hidalgo Drive, Poblacion, City of Makati,
Fourth District, NCR, Philippines, 1210
(63) 918 990 1315

For future information:
Email: monzone@singnet.com.sg
Website: www.monzonegroup.com

Monzone Customer Hotline
(65) 6365 1315 (24/7)
(6016) 262 1315 (24/7)



Thermo King – by Trane Technologies (NYSE: TT), a global climate innovator – is a worldwide leader in sustainable transport temperature control solutions. Thermo King has been providing transport temperature control solutions for a variety of applications, including trailers, truck bodies, buses, air, shipboard containers and railway cars since 1938. For more information, visit www.thermoking.com or www.tranetechnologies.com.

Asia Pacific Headquarters & China Office
8-12F, L'Avenue Shanghai,
99 Xianxia Road, Shanghai, 200051, P.R.C
Tel: +86 21 2221 5000
Fax: +86 21 2221 5409

Global Headquarters
314 West 90th Street
Minneapolis, Minnesota, 55420, U.S.A.
Tel: +1 952 887 2200
Fax: +1 952 887 2529

Thermo King customer service hotline

 **800-820-2828**

 **400-820-7972**



New Generation Ultra-thin Electric Trailer Refrigeration Unit – THOR Series

TH-450

Key Features

Design | More Excellent

- TH series appearance, family design
- Slim and compact structure, low wind resistance and streamlined appearance
- Integrated insulation casing of evaporator, no air/heat leakage

Performance | More Outstanding

- R410A refrigerant
- Inverter scroll compressor, higher efficiency
- Electronic expansion valve throttling, rapid cooling
- EVI technology provides higher freezing capacity and reliability

Electrical Control | More Intelligent

- Shared Arcon platform, equipped with new VP controller
- Precise temperature control $\pm 0.5^{\circ}\text{C}$ (return air)
- Remote information processing module, real-time recording of operating data

Power Supply | More Options

- 380V AC vehicle power supply or standby power supply
- 350~750V DC battery (optional)

Maintenance | More Convenient

- Integrated control box, easy to repair
- Axial flow fan, easy to maintain
- Wireless remote upgrade

Installation | More Flexible

- Perfectly matches standard land transport trailer bodies
- Can provide matching sea container installation solutions (optional)

Safety | More Reliable

- Robust control to keep running with failures
- Brushless fan with a lifespan of over 30,000 hours
- Jet enthalpy compressor ensures the reliability of the unit in extreme environments



THOR Series Control Panel (Standard)

- Integrated CAN and RS485 communication, easy to expand
- Supports online program upgrade
- Can store 1 year of operating data
- IP65, no fear of wind and rain



Cabin Remote Panel (Optional)



Key Parameters

Unit Model	TH-450	
------------	--------	--

Cooling Capacity (ATP condition, ambient temperature 30°C)

Cabin Temperature	$^{\circ}\text{C}$	0	-20
Cooling Capacity	W	20,000	12,000
Refrigerant	-	R410A	

Air Volume (0 Pa static pressure)

Air Volume	m^3/h	7,000 (MAX)
------------	-----------------------	-------------

Weight and Dimensions

Weight	KG	350
Dimensions (H*W*D)	mm	1590*2056*506

Power Input and Consumption

Maximum Consumption	kW	18
Power Input	-	380V/3PH/50HZ (three-phase four-wire)
Voltage Range	V	340~437 VAC
Recommended Engine Power	KVA	30

